



PRODUCT SPECIFICATION

1. PRODUCT CODE : DMC4702

2. DESCRIPTION : 4 core 7/2 pcw v75 insulated Aluminium / Polyester tape screened including a 7/2 tinned drain wire V75c PVC sheathed.
AUSTEL A93/CA/0123
Extra low voltage use ,not for mains connection.

3. CONSTRUCTION

3.1 CONDUCTOR : 7 strands of 0.2mm nom. Annealed Copper to AS1125 drawn from Class 110A copper to AS1574.
Max. D.C. resistance at 20C : 89.5 ohms / klm

3.2 INSULATION : Coloured P.V.C to AS3808 type V75.

Nominal Diameter : 1.15 mm
Nom. Wall Thickness: 0.26 mm

3.3 LAY UP : 4 cores twisted.
1.Red 2.Blue 3. White 4. Black .

3.4 SCREEN : Aluminium / Polyester tape screen in contact along its length with a 7/2 TACW drain wire.

3.5 SHEATH : Coloured P.V.C. to AS3808 type 4V75

Nominal Diameter : 4.55 mm
Nom. Wall Thickness : 0.76 mm

3.6 IDENTIFICATION :

Legibly and Durably printed at nom. 1M intervals :

“TYCAB AUSTRALIA MULTICORE DATA DMC4702 CCL A93/CA/0123”

As at 10/3/05