



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

- 1. PRODUCT CODE** LFX24802
- 2. DESCRIPTION** 2 Core Parallel Webbed Figure 8 48/0.2 (1.5mmsq). P.A.C.W.
CLEAR P.V.C insulated.
Extra Low Voltage. Not for mains outlet connection.
Oxygen Free copper. RoHS compliant PVC.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** 48 strands of 0.2mm Plain Annealed Copper to AS/NZS 1125 drawn from Class 102 copper to AS/NZS 1574.
Max. D.C. resistance at 20C: 13.3 ohms / km
- 3.2 INSULATION:** CLEAR P.V.C. 75C min. rating
Parallel Webbed (Figure 8) construction
Nominal Diameter: 3.1 x 6.5 mm
Nominal Wall Thickness: 0.7 mm
- 3.3 IDENTIFICATION:** Polarity by coloured stripe on one leg as per customer request.