





TYCAB New Zealand LTD
H1Z2Z2-K2X4MM2-BK-100

Approval Sheets

TYPE	EN50618/IEC62930	DOC.REF	TY2023
Cross-Section	H1Z2Z2-K/IEC62930 2X4mm2	Edition	A/0
			
Wire&Cable Construction		Electrical Properties	
Conductor		Voltage rating: AC 0.6/1KV,DC 1.5KV	
Construction Item(units)	4mm2	Temperature rating: -40~90°C	
Construction(mm)	56/0.285±0.008	Dielectric strength: AC-6.5kV/5min	
Material	class 5 tinned copper wire	Spark test: AC-10kV/In the air	
O.D(mm)	2.45	Conductor resistance: 5 .09ΩKM Max at20°C	
Insulation		Weathering/UV-resistance: 720h, No cracking	
Material	XLPO	Physical Properties	
Avg.Thick(mm)	0.70	Elongation of unaged values(%)≥ 125%	
Min.Thick(mm)	0.50	Insulation Tensile strength of unaged values (N/mm2): ≥6.5;	
O.D(mm)	4.2±0. 15	Jacket Tensile strength of unaged values (N/mm2):≥ 8.0	
Color	Red /Black	Aged in a full draft circulating air oven: 150±2.0°C	
Jacket		Elongation of After aging(%)≤30%	
Material	XLPO	Tensile strength of After aging: ≤30%	
Avg.Thick(mm)	0.80	Ozone resistance: 25±2°C*24h No cracking	
Min.Thick(mm)	0.60	Cold bend test: -40±2°C*16h No cracking	
O.D(mm)	5.5±0.2*11.4±0.6	Cold impact test: -40°C*16h/1000g; 100mm No cracking	
Color	Black	Flame test: iec60332	
Surface	/		
Marking			
NINGBO HAISHU TIANYU CABLES & WIRE CO., LTD 2023 R50549391 IEC131-2X4mm ² 0.6/1KV AC 1.5KV DC SOLAR CABLE TÜV 62930 IEC 131 - DC USE ONLY - DO NOT DISCONNECT UNDER LOAD 001M...100M			