



Tycab NZ Limited
102A Carbine Road
Mt Wellington
AUCKLAND 1644
Ph. 64 9 573 1990

PRODUCT SPECIFICATION

3 Core 0.75mm Flexible Cord

1. PRODUCT CODE FMC32402

2. DESCRIPTION 3 Core 24/.20 (0.75mm sq. 7.5 AMP) .P.C.W. V90 PVC insulated. 5V90 P.V.C. sheathed. Flexible cord.
250/440 Volt to AS/NZS3191 APPROVAL V98005

3. CONSTRUCTION

3.1 CONDUCTOR: 24 strands of 0.20 mm Annealed Copper to AS/NZS1125 drawn from Class 102 copper to AS/NZS1574.
Max. D.C. resistance at 20C: 26.07ohms / klm

3.2 INSULATION: Coloured V90 PVC to AS/NZS3808
Nominal Diameter: 2.3 mm
Nom. Wall Thickness: 0.6 mm

3.3 LAY UP: 3 Cores laid up.
1. Brown 2. Blue 3. Green/Yellow

3.4 SHEATH: Coloured P.V.C. type 5V90 to AS/NZS3808.
Nominal Diameter: 6.7 mm
Nom. Wall Thickness: .8 mm

3.5 IDENTIFICATION:
Indented into Sheath at intervals not exceeding 500mm.

“TYCAB V98005 V90 250/440 ORDINARY DUTY “