




TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION



1. PRODUCT CODE LDX278402

2. DESCRIPTION 2 X 784/.2 (25mmsq). P.A.C.W.
V90HT P.V.C Insulated & Clear PVC Sheathed in Figure 8 format.
Insulated cores to AS/NZS5000 0.6/1KV.
Low Voltage, Not for Mains Connection.

3. CONSTRUCTION

3.1 CONDUCTOR: 784 strands of 0.2mm Plain Annealed Copper to JISC3102
& AS/NZS1125 drawn from Class 102 copper to AS/NZS1574.

Max. D.C. resistance at 20C: 0.78 ohms / km

3.2 INSULATION: Coloured V90HT P.V.C. to AS/NZS3808
Nominal Diameter: 8.7 mm
Nominal Wall Thickness: 1.2 mm

3.3 CORE COLOURS: 1. Blue
2. Red

3.4 SHEATH: Clear V90HT PVC to AS/NZS3808
Figure 8 (parallel webbed) configuration

Nominal Dimensions: 11.0 x 23.0 mm
Nominal Wall Thickness: 1.1 mm

AUSTRALIAN MADE CABLES LEADING THE WAY