



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1. PRODUCT CODE LFD232202

2. DESCRIPTION 2 Core Parallel Webbed (Figure 8) 322/0.2 (10.0mmsq). P.A.C.W.
FLEXIBLE U.V resistant P.V.C insulated.
Extra Low Voltage cable.
Not for mains outlet connection.

3. CONSTRUCTION

3.1 CONDUCTOR: 322 strands of 0.2mm Plain Annealed Copper to AS/NZS 1125 drawn from Class 110A copper to AS/NZS 1574.

Max. D.C. resistance at 20C: 1.83 ohms / km

3.2 INSULATION: Black U.V Resistant P.V.C.
Parallel Webbed (Figure 8 configuration).

Nominal Diameter: 6.0 x 12.5 mm

Nominal Wall Thickness: 0.66 mm

3.3 POLARITY IDENTIFICATION: By permanent raised ribs on one leg.

3.4 PRINTING: On the sheath and metre marked

TYCAB GARDEN LIGHTING 2X10 MMSQ 001M >|<

AUSTRALIAN MADE CABLES LEADING THE WAY