



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION



- 1. PRODUCT CODE:** MWS22603
- 2. DESCRIPTION** 2 Core Flat Twin Sheathed 23/.32 (1.84mmsq). Tinned Copper Wire.
V90 Insulated & 5V90 Sheathed.
Extra Low Voltage. Not for Mains GPO Connection.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** 23 strands of 0.32mm Tinned Annealed Copper to AS/NZS1125 drawn from Class 110A copper to AS/NZS1574.
Max. D.C. resistance at 20C: 10.2 ohms / km
- 3.2 INSULATION:** Coloured V90 P.V.C. to AS/NZS3808.
Nominal Diameter: 2.6 mm
Nominal Wall Thickness: 0.4 mm
- 3.3 CORE COLOURS** 1. Red
2. Black
Laid parallel.
- 3.4 SHEATH:** Coloured 5V90 to AS/NZS3808
Flat configuration
Nominal Dimensions: 3.8 x 6.3 mm
Nominal Wall Thickness: 0.6 mm

AUSTRALIAN MADE CABLES LEADING THE WAY